

4CH 1.0MP CCTV WIFI KIT

Features

- 720P waterproof WIFI IP Camera;36 IR Leds
- IPC connect the NVR automatically,Easy connection
- Strong WIFI signal,Not drop
- P2P Cloud services
- Support Motion detection, Plug and play
- support mobile phone (iOS&android) monitoring
- Remote control, Playback, Preview
- Support Multi-user online access
- More than 100 meters with no obstacle, More than 30 meters if penetrate the wall



IP Camera Specification

	UL-KIT1.0MP-BMIP/4CH-WIFI
Image sensor	1/4" 1.0M Pixel CMOS
Min. Illumination	Color: 0.05Lux@(F1.5, AGC ON) B/W: 0.001Lux@(F1.5, AGC ON,IRled ON)
S / N ratio	≥39dB
Shutter speed	1/5 - 1/20,000s,
Day & Night	Day / Night / External control (IR Cut Filter)
AGC	Auto / Manual
White balance	Auto/Manual /ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp
Wide dynamic range	Digital Wide dynamic range
Digital noise Reduction	DNR,3DNR
Video Compression	H.264 Main Profile/M-JPEG
Audio Compression	G711, PCM
Max.Image Resolution	1280x720@30fps
Image Resolution	1280×720, 720×576, 640×480
Bitrate	CBR/VBR, bitrate: 32Kbps~10Mbps variable
Motion detect	Support
Privacy Zone Masking	4 privacy masks programmable
P2P	Android, IOS
Protocols	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, P2P
Onvif	Non- Support
Network	10/100M Base-TX Ethernet, RJ45 Connector
Wireless	Frequency:2.4G
	transmission distance :More than 100 meters with no obstacle, More than 30 meters if penetrate the wall, The actual transmission distance according to the situation
Power	12VDC@1A
Working Temperature	-30°C ~60°C, Humidity≤90%RH(Unsupported-condensing)

NVR Specification

		UL-KIT1.0MP-BMIP/4CH-WIFI
System	Main processor	HISI
	Operating System	Embedded Linux
Video	Video compression	H.264 High Profile Level 4.2
	Video output	720P60,XGA,1080P60
	Video input(IP)	4*1080P/4*960P/4*720P
Audio	Audio compression	G.711
	intercom	None
Record & playback	Recording mode	Manual/Alarm/Video Detection/Continuous
	Local Playback	1*1080P
Storage & Backup	Record Storage	network
	Backup mode	Network backup, USB hard disk
Network Control	Protocol	TCP/IP,HTTP,DHCP,UDP,RTP,RTSP,FTP,NTP,ONVIF,SADP(IP),P2P
Interface	Video output	1ch HDMI, 1ch VGA output
	Audio I/O	None
	Alarm I/O	None
	Network interface	1*RJ45 10M/100M/1000M Adaptive Ethernet port
	USB	2*USB 2.0 port
	Hard disk	1SATA(Up to 4TB)
Other	Power supply	DC +12V /2A
	Power Consumption	5W(Without HDD)
	Work environment	Temperature:-10°C~+55°C, Humidity:10%-90%RH