

## 4CH 2.0MP CCTV KIT



### Features

- 4 x 1080P bullet outdoor camera.
- 4ch 1080P 5 in 1 DVR (AHD / TVI / CVI / IP / CVBS).
- 18m CCTV cables.
- Remote control & mouse.
- P2P function through “Camview” mobile Apps.

DVR Model	UL-KIT2.0MP-BPA/4CH
<b>Video &amp; Audio Input</b>	
Video Input	4 channel
Resolution	Analog+IP camera(PAL): 4 * 1080P/15 + 0; 4 * 1080N/25 + 0; 2 * 1080P/25 + 2 * 1080P/25 ; 0 + 4 * 1080P/25
Audio input	4channel,BNC
Video input Interface	BNC(1.0Vp-p,75Ω)
Video compression	H264
Audio compression	G.711a
Bidirectional talk	Support
<b>Display</b>	
Interface	1 HDMI, 1 VGA
User interface	support 16-bit true color graphical menu interface and mouse operation
Resolution	1024*768;1280*720;1280*1024;1440*900;1920*1080
Display Split	1/4
OSD	Channel title, Time, Video loss, Camera lock, Motion detection, Recording
<b>Recording</b>	
Record Mode	Manual, Auto(Regular(Continuous), MD, Alarm), Off
Record Interval	1~120min (default: 60 min), Pre-record: 1~30sec
<b>Alarm</b>	
Trigger Events	Recording, Alarm, Video Push, Email, Buzzer
Video Detection	Motion Detect, Video Blind, Video Loss
Abnormal	HDD loss, Low HDD capacity, Net disconnection, IP conflict, HDD error
<b>Playback &amp; Backup</b>	
Sync Playback	2* 1080P/15fps; 4 * 1080N/15 fps; 2 * 1080P/25fps
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second)
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network

<b>Network</b>	
Ethernet	RJ-45 port, 10/100M
Network Functions	HTTP, TCP/IP, UPNP, DHCP, DNS, PPPOE, DDNS, FTP, P2P.
Mobile Phone	CamViews, (IPhone, IPad, Android)
Max.User Access	10 users
<b>Storage</b>	
Internal HDD	1 SATA ports, up to 4TB
<b>Auxiliary</b>	
USB Interface	2 ports, USB2.0
RS485	1 port, For PTZ control
<b>General</b>	
Power Supply	AHD: DC12V/2A
Power Consumption	20W(without HDD)
Working Environment	-10 ~+55°C / 10~90%RH / 86~106kpa
Dimension(W*D*H)	1U, 255*244*47mm
Weight	1.0-1.5kg(without HDD)
Camera Model	UL-KIT2.0MP-BPA/4CH
Image Sensor	1/3" 2.0M CMOS Sensor
Resolution	1920(H)X1080(V)
System Mode	PAL/NTSC
Lens	3.6mm
IR Distance	20M/24LED
Day/Night	Auto ICR
Minimum illumination	0.1 lux IR LED on: 0 lux
S/N Ratio	48dB or more
Gamma	0.45
BLC	Auto
Electronic Shutter	Auto:1/50(1/60)-1/100,000Sec
White Balance	Auto
Video Output	1.0Vp-p,75Ω , BNC
Power Supply	DC12V / 500mA
Working Temperature	-20°C—50°C